



## ► DPF 210 Polyester Roll-Up Banner

### Digital Print Banner

DPF 210 is a 9.8-mil (250 micron) premium, semi-rigid, coated polyester banner that is used in roll-up or pop-up banner applications. It has a gray, block-out layer that provides excellent opacity. DPF 210 is available in satin and pebble texture finishes, and yields high print resolution and image quality. It also has excellent lay-flat properties with minimal edge-curl. DPF 210 is compatible with Eco-Solvent, Solvent or Latex\* inks. DPF 210 is rated for indoor durability up to 1 year. Please use proper handling and correct profiles with appropriate heater settings for optimal prints.

### APPLICATIONS & FEATURES

- Digital printing with a wide variety of direct print systems
- Indoor roll-up and pop-up display systems
- Exhibitions, advertisements and POP displays

### PERFORMANCE & PHYSICAL DATA

| PROPERTY                      | TEST METHODS   | TYPICAL VALUE                                |
|-------------------------------|--|--|
| WEIGHT                        | Internal Test Method                                       | 510 +/- 20 gram/sqm<br>(15 +/- 0.25 oz/sqyd) |
| THICKNESS                     | Micrometer, Federal Bench Type                             | 9.8-mil (250 micron)                         |
| COLOR                         | CIELAB   | Max DE 1.0 from color standard               |
| OPACITY / CONTRAST RATIO      | Internal Test Method                                       | 90% - 100%                                   |
| GLOSS                         | Gloss Meter at 60° Reflection                              | < 15 Gloss Units                             |
| TENSILE STRENGTH (WARP, WEFT) | ASTM D-882   | Min. 100 lbs/in, 125 lbs/in                  |
| ELONGATION (WARP, WEFT)       | ASTM D-882   | Min. 150%, 25%                               |
| TEAR STRENGTH (WARP, WEFT)    | ASTM D-1004  | Min. 15 lbs/in                               |
| PRINTING                      | Internal Test Method                                       | Eco-Solvent, Solvent, Latex*                 |
| SHELF LIFE (IN BOX)           | Free from excessive moisture, temperature, direct sunlight | 1 year from production date                  |
| STORAGE TEMPERATURE           | Internal Test Method                                       | 85°F or lower                                |

Standard Terms & Conditions Apply




\*Compatible with HP 360 Latex







## TERMS & CONDITIONS

*The following is made in lieu of all warranties expressed or implied:*

All statements, technical information and recommendations published by Arlon relating to Arlon products are based on tests believed to be reliable and within the accuracy of the equipment used to obtain the specific values. Their accuracy or completeness is not guaranteed and Arlon makes no warranty with regard thereto. Seller's and manufacturer's only responsibility shall be to replace any quantity of the product proved defective. Seller and manufacturer shall not be liable for injury, loss or damage, direct or consequential, arising out of use or the inability to use the product. Nor shall seller or manufacturer be liable for any costs or expenses incurred in the processing or printing on the product. Before using, user shall determine the suitability of the product for its intended use. User assumes all risk and liability of every nature in connection therewith. No statements or recommendations other than those contained in the technical information published by Arlon shall have force or effect unless contained in an agreement manually signed by the officers of seller and manufacturer.

December 2016

USA:  200 Boysenberry Lane, Placentia, CA 92870, USA  
EUROPE:  North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands  
UK:  P6 Parklands, Heywood Distribution Park, Heywood, Lancashire OL102TT, UK

 800 232 7161/+1 714 985 6300  800 329 2756  
 +31 70 354 4311  +31 70 355 7721  
 +44 161 884 0592  +31 70 355 7721

arlon.com