



Hi-Stat® cling vinyl is a very soft, flexible vinyl which adheres to most clean, high polished smooth surfaces without adhesive.

Hi-Stat

Repositionable – printed decals can be reused if properly handled

Easy removal without leaving a trace of residue behind

No solvents are needed for application or removal

Can be wet applied

For indoor and outdoor use

Made in the U.S.A.

Available in 8 mil white and clear on a 8 pt stayflat paper board liner

Print Compatibility: HP Indigo, Conventional and UV Offset

Easy to apply and remove from these surfaces:



Applications

Window Advertising

P.O.P. Window Decals

Price Stickers

Automotive Window Decals

LED Screen Protection



STOCKED PRODUCTS ▶

HP Indigo	Finish/Color	SKU #	Size	Thickness	GSM	M Wgt	Sheets/Carton
Gloss White		SPMHSWIN1218	12" x 18"	8 mil	405	123.3	300
		SPMHSWIN1319	13" x 19"			140.0	
Gloss Clear		SPMHSCIN1218	12" x 18"	8 mil	390	123.3	300
		SPMHSCIN1319	13" x 19"			140.0	

Custom Size Offering: Custom converted sheet and roll options available to meet your specific requirements



Nekoosa has 3 conveniently located converting facilities for quick shipping of custom sheets.

TECHNICAL DATA ▶

Physical Properties

Adhesive	None
Film	Flexible Vinyl
Finish	High Gloss
Color	White and Clear
Liner	Paper Board
Film Thickness	8 mil (7.5 ± 0.2 mil)
Liner Thickness	8 pt
Weight	.62#
Adhesion	N/A
Surface Tension	32 Dynes Minimum

Conditions for Use

Shelf Life	1 year*
Min. Application Temp.	50° F (10° C)
Service Temp. Range	-10° F to 120° F (-23.3° C to 48.9° C)
Outdoor Durability	3 Months**
Indoor Durability	6 months
Water Resistance	Excellent
Chemical Resistance	Excellent***
Material Reuse	Yes†

*When stored at 75° F and 50% relative humidity.

**Mid-continental USA vertical exposure.

***Excellent - commercial window cleaners.

†Printed decals can be reused if properly handled.

Certified for
HP Indigo

The information provided herein is correct to the best of Nekoosa's knowledge. No liability for any errors, facts or opinions are accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.